ースにのアレヘハモTi

AKT690TNG

Ventilated refrigerated cabinet with glass door













- · Stainless steel external and internal structure
- · Ventilated refrigeration with incorporated refrigeration unit
- · Digital control unit
- Extractable refrigeration monoblock unit
- Door frame with thermal break
- Automatic defrost
- Automatic condensation evaporation
- Double glazed door
- 70 mm insulation thickness
- · Door with ergonomic handles
- · Easily removable magnetic gasket
- Internal rounded edges
- Internal LED strip lighting
- Door with key lock
- External bottom and back panels in galvanized steel
- · Adjustable stainless steel feet
- Equipped with 3 GN2/1 shelves
- 4 casters kit (2 of which with brake) model RBA7 available on request

TECHNICAL FEATURES

MODEL	AKT690TNG
ENERGY CLASS	B (2019/2018/UE)
POWER WATT	230
POWER SUPPLY	230/IN/50
TEMPERATURE °C	0 ÷ +8
REFRIGERANT	R290
MAX. TEMP. / HUMIDITY	+30 °C / 55% HR
DIMENSIONS MM	740x828x2050h
INTERNAL DIMENSIONS MM	600x690x1475h
CAPACITY L	650
SHELVES NO. AND TYPE	3 x GN2/1
NET WEIGHT KG	120
GROSS WEIGHT KG	134
PACKING DIMENSIONS CM	76x88x207h