


AKT690BTG

Ventilated refrigerated cabinet with glass door



- Stainless steel external and internal structure
- Ventilated refrigeration with incorporated refrigeration unit
- Digital control unit
- Extractable refrigeration monoblock unit
- Door frame with thermal break
- Automatic defrost
- Automatic condensation evaporation
- Triple glazed door
- 70 mm insulation thickness
- Door with ergonomic handles
- Easily removable magnetic gasket
- Internal rounded edges
- Internal LED strip lighting
- Door with key lock
- External bottom and back panels in galvanized steel
- Adjustable stainless steel feet
- Equipped with 3 GN2/1 shelves
- 4 casters kit (2 of which with brake) model RBA7 available on request

TECHNICAL FEATURES

MODEL	AKT690BTG
ENERGY CLASS	D (2019/2018/UE)
POWER WATT	440
POWER SUPPLY	230/1N/50
TEMPERATURE °C	-15 ÷ -20
REFRIGERANT	R290
MAX. TEMP. / HUMIDITY	+30 °C / 55% HR
DIMENSIONS MM	740x828x2050h
INTERNAL DIMENSIONS MM	600x690x1475h
CAPACITY L	650
SHELVES NO. AND TYPE	3 x GN2/1
NET WEIGHT KG	130
GROSS WEIGHT KG	143
PACKING DIMENSIONS CM	76x88x207h