




## AKT4206TN

Ventilated refrigerated GNI/1 counter with 4 doors and raised back



- Stainless steel external and internal structure
- 10 cm raised back
- Ventilated refrigeration with incorporated refrigeration unit
- Ducted ventilation
- Digital control unit
- Extractable refrigeration monoblock unit
- Anticorrosion treated evaporator
- Door frame with thermal break
- Automatic defrost
- Automatic condensation evaporation
- 70 mm insulation thickness
- Easily removable magnetic gaskets
- Internal rounded edges
- Service compartment with key lock
- External bottom and back panels in galvanized steel
- Adjustable stainless steel feet
- Equipped with 4 GNI/1 shelves
- 6 casters kit (3 of which with brake) model RBA8 available on request
- 2 drawers kit (model SET2-6) available on request

- 3 drawers kit (model SET3-6) available on request

## TECHNICAL FEATURES

<b>MODEL</b>	AKT4206TN
<b>ENERGY CLASS</b>	C (2015/1094/UE)
<b>CLIMATE CLASS</b>	4
<b>POWER WATT</b>	340
<b>POWER SUPPLY</b>	230/1N/50
<b>TEMPERATURE °C</b>	0 ÷ +8
<b>REFRIGERANT</b>	R290
<b>MAX. TEMP. / HUMIDITY</b>	+40 °C / 60% HR
<b>DIMENSIONS MM</b>	2250x700x950h
<b>INTERNAL DIMENSIONS MM</b>	1710x550x575h
<b>CAPACITY L</b>	541
<b>SHELVES NO. AND TYPE</b>	4 x GN1/1
<b>NET WEIGHT KG</b>	118
<b>GROSS WEIGHT KG</b>	137
<b>PACKING DIMENSIONS CM</b>	228x72x98h