



AKTS2106TN

Ventilated refrigerated counter with 2 doors, depth 600 mm



- Stainless steel external and internal structure
- Ventilated refrigeration with incorporated refrigeration unit
- Ducted ventilation
- Digital control unit
- Extractable refrigeration monoblock unit
- Anticorrosion treated evaporator
- Door frame with thermal break
- Automatic defrost
- Automatic condensation evaporation
- 70 mm insulation thickness
- Easily removable magnetic gaskets
- Internal rounded edges
- Service compartment with key lock
- External bottom and back panels in galvanized steel
- Adjustable stainless steel feet
- Equipped with 2 330x430 mm shelves
- 4 casters kit (2 of which with brake) model RBA7 available on request

TECHNICAL FEATURES

MODEL	AKTS2106TN
ENERGY CLASS	C (2015/1094/UE)
CLIMATE CLASS	4
POWER WATT	250
POWER SUPPLY	230/1N/50
TEMPERATURE °C	0 ÷ +8
REFRIGERANT	R290
MAX. TEMP. / HUMIDITY	+40 °C / 60% HR
DIMENSIONS MM	1350x600x850h
INTERNAL DIMENSIONS MM	830x450x575h
CAPACITY L	215
SHELVES NO. AND TYPE	2 x 330x430 mm
NET WEIGHT KG	66
GROSS WEIGHT KG	74
PACKING DIMENSIONS CM	140x62x88h