




AKTS4106TN

Ventilated refrigerated counter with 4 doors, depth 600 mm



- Stainless steel external and internal structure
- Ventilated refrigeration with incorporated refrigeration unit
- Ducted ventilation
- Digital control unit
- Extractable refrigeration monoblock unit
- Anticorrosion treated evaporator
- Door frame with thermal break
- Automatic defrost
- Automatic condensation evaporation
- 70 mm insulation thickness
- Easily removable magnetic gaskets
- Internal rounded edges
- Service compartment with key lock
- External bottom and back panels in galvanized steel
- Adjustable stainless steel feet
- Equipped with 4 330x430 mm shelves
- 6 casters kit (3 of which with brake) model RBA8 available on request

TECHNICAL FEATURES

MODEL	AKTS4106TN
ENERGY CLASS	D (2015/1094/UE)
CLIMATE CLASS	4
POWER WATT	340
POWER SUPPLY	230/1N/50
TEMPERATURE °C	0 ÷ +8
REFRIGERANT	R290
MAX. TEMP. / HUMIDITY	+40 °C / 60% HR
DIMENSIONS MM	2250x600x850h
INTERNAL DIMENSIONS MM	1710x450x575h
CAPACITY L	442
SHELVES NO. AND TYPE	4 x 330x430 mm
NET WEIGHT KG	102
GROSS WEIGHT KG	114
PACKING DIMENSIONS CM	228x62x88h