
## **ースにのアレヘハモTi**


## AKD600RG














- · White painted steel external structure
- · ABS internal structure
- · Cooling plate static refrigeration with fan to uniform the temperature
- · Door integrated digital control unit
- Stop compressor defrost
- Automatic condensation evaporation
- · Double glazed door with plastic frame
- 40 mm insulation thickness
- · Easily removable magnetic gasket
- Internal rounded edges
- Internal LED lighting with ON/OFF switch
- Door with key lock
- Equipped with 3 650x525 mm and 1 650x335 mm shelves
- Interal guides compatible with GN2/1 pans and shelves

## TECHNICAL FEATURES

| MODEL                  | AKD600RG         |
|------------------------|------------------|
| ENERGY CLASS           | B (2019/2018/UE) |
| POWER WATT             | 130              |
| POWER SUPPLY           | 230/IN/50        |
| TEMPERATURE °C         | +2 ÷ +8          |
| REFRIGERANT            | R600a            |
| MAX. TEMP. / HUMIDITY  | +33 °C / 60% HR  |
| DIMENSIONS MM          | 777x710x1895h    |
| INTERNAL DIMENSIONS MM | 650x530x1620h    |
| CAPACITY L             | 580              |
| SHELVES NO. AND TYPE   | 3 x 650x525 mm   |
|                        | 1 x 650x335 mm   |
| NET WEIGHT KG          | 106              |
| GROSS WEIGHT KG        | 122              |
| PACKING DIMENSIONS CM  | 84x76x201h       |