




AKTU2106TN

Ventilated refrigerated GNI/1 counter with 2 doors, height 650 mm



- Stainless steel external and internal structure
- Ventilated refrigeration with incorporated refrigeration unit
- Ducted ventilation
- Digital control unit
- Extractable refrigeration monoblock unit
- Anticorrosion treated evaporator
- Door frame with thermal break
- Automatic defrost
- Automatic condensation evaporation
- 70 mm insulation thickness
- Easily removable magnetic gaskets
- Internal rounded edges
- External bottom and back panels in galvanized steel
- Adjustable stainless steel feet
- Equipped with 2 GNI/1 shelves
- 4 casters kit (2 of which with brake) model RBA7 available on request
- 2 drawers kit (model SET2-6) available on request

TECHNICAL FEATURES

MODEL	AKTU2106TN
ENERGY CLASS	C (2015/1094/UE)
CLIMATE CLASS	4
POWER WATT	250
POWER SUPPLY	230/1N/50
TEMPERATURE °C	0 ÷ +8
REFRIGERANT	R290
MAX. TEMP. / HUMIDITY	+40 °C / 60% HR
DIMENSIONS MM	1350x700x650h
INTERNAL DIMENSIONS MM	830x550x375h
CAPACITY L	171
SHELVES NO. AND TYPE	2 x GN1/1
NET WEIGHT KG	56
GROSS WEIGHT KG	64
PACKING DIMENSIONS CM	140x72x68h