ースにのアレヘハモTi


AKTU4106TN















- Stainless steel external and internal structure
- · Ventilated refrigeration with incorporated refrigeration unit
- Ducted ventilation
- Digital control unit
- Extractable refrigeration monoblock unit
- Anticorrosion treated evaporator
- Door frame with thermal break
- Automatic defrost
- Automatic condensation evaporation
- 70 mm insulation thickness
- · Easily removable magnetic gaskets
- · Internal rounded edges
- External bottom and back panels in galvanized steel
- Adjustable stainless steel feet
- Equipped with 4 GN1/1 shelves
- 6 casters kit (3 of which with brake) model RBA8 available on request
- 2 drawers kit (model SET2-6) available on request

TECHNICAL FEATURES

MODEL	AKTU4106TN
ENERGY CLASS	D (2015/1094/UE)
CLIMATE CLASS	4
POWER WATT	250
POWER SUPPLY	230/IN/50
TEMPERATURE °C	0 ÷ +8
REFRIGERANT	R290
MAX. TEMP. / HUMIDITY	+40 °C / 60% HR
DIMENSIONS MM	2250x700x650h
INTERNAL DIMENSIONS MM	1710x550x375h
CAPACITY L	353
SHELVES NO. AND TYPE	4 x GN1/1
NET WEIGHT KG	89
GROSS WEIGHT KG	101
PACKING DIMENSIONS CM	228x72x68h